

**(19) World Intellectual Property Organization
International Bureau**



(43) International Publication Date
17 October 2002 (17.10.2002)

PCT

(10) International Publication Number
WO 02/082858 A2

(51) International Patent Classification⁷: H04R 23/00

(74) Agent: SCHRIJNEMAEEKERS, Hubert, J., M.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number: PCT/IB02/00973

(22) International Filing Date: 20 March 2002 (20.03.2002)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
01201292.8 4 April 2001 (04.04.2001) EP


(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors: **AARTS, Ronaldus, M.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **JOHNSON, Mark, T.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

[Continued on next page]

(54) Title: SOUND AND VISION SYSTEM



(57) Abstract: A sound and vision system comprising a display device (1) and an acoustic transducer means, such as a loudspeaker or a microphone. The display device includes display cells (9) having opposite electrodes (7, 8) and includes a conductive means (11) connected to the electrodes in order to address said display cells. The acoustic transducer means is formed by a display cell and the conductive means is electrically coupled to the acoustic transducer means in order to convey signals, as a result of which the acoustic transducer means is an integral part of the display device.

WO 02/082858 A2



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Sound and vision system

The invention relates to a sound and vision system comprising a display device and an acoustic transducer means.

The invention further relates to an electronic apparatus including such a system.

5 The patent application WO-A/00/69212 discloses a small portable electronic article for personal use, such as a personal organizer or a mobile telephone, which article comprises a casing provided with a keyboard or keypad, a visual display and a transparent cover over the display. The electronic article further comprises a loudspeaker composed of the transparent cover and a vibration exciter mounted on the transparent cover, the
10 transparent cover thus serving as an acoustic radiator. Although the loudspeaker is incorporated in the known small personal portable electronics article in order to reduce weight and volume of the article, the possibilities to reduce e.g. weight and volume seem to be not fully exploited.

15 It is an object of the invention to provide a sound and vision system in which the acoustic transducer means is further integrated in the system.

 This object is achieved by the sound and vision system according to the invention, as defined in Claim 1, i.e. a system comprising a display device and an acoustic transducer means, which display device includes display cells having opposite electrodes and includes a conductive means connected to the electrodes in order to address said display
20 cells, wherein the acoustic transducer means includes one or more of said display cells and the conductive means is electrically coupled to the acoustic transducer means. It is assumed that it is known that a display comprises a display electronic means for selecting and controlling the display cells, the display electronic means including said conductive means and the display cells of the display device incorporating electro-optical devices. In the sound
25 and vision system according to the invention the acoustic transducer means is virtually an integral part of the display device, the display electronic means, particularly its conductive means, being used for making an electrical connection to the acoustic transducer means for transmission of electrical signals to and/or from the acoustic transducer means.

The invention is based on the insight that it is possible to provide a sound and vision system with an acoustic transducer means by only or mainly making use of components already present in a known display device, without any significant loss of performance of the vision function itself. Due to the feature as defined in Claim 1, which is the result of this insight, the number of components is reduced as compared with the known article and further miniaturization of sound and vision systems is achieved. In general, the frequencies typically used to display visual data on a display screen only include low frequencies, particularly the 50-60 Hz frame refresh rate, and very high frequencies, particularly the data rate beyond 100 kHz. These frequency ranges fall outside the acoustic band normally used for speech audio of e.g. a telephone, particularly 300 Hz –3400 Hz, and practically fall outside the range of high performance audio, particularly up to 20 kHz. Thus, a video addressing does not produce any undesired audio output, whilst on the other hand the display cells can be excited at intermediate audio frequencies without interfering with the video signals. It is to be noted that it is conceivable to use only the sound function of the system according to this invention.

An embodiment of the sound and vision system according to the invention is characterized in that the display device is a liquid crystal display device including a liquid crystal layer sandwiched between substrates. Especially liquid crystal materials -and effects- which exert a strong mechanical force on the substrate are useful. Suitable examples of such materials are (anti)ferro electric liquid crystals, flexo electric liquid crystals and cholesteric texture liquid crystals. A prior art liquid crystal display device is disclosed in US-A 4,723,838 (herewith incorporated by reference).

An embodiment of the system according to the invention is characterized in that the display device is an electrochromic display device including a material of which the color is switchable in dependence on an electric current or potential. A prior art electrochromic display device is disclosed in the article Nanocrystalline Electrochromic Devices, pages 1-3; <http://dcwww.epfl/lpi/electr.html> (herewith incorporated by reference).

An embodiment of the system according to the invention is characterized in that the display device is an electrophoretic display device including an electrophoretic display medium sandwiched between conductors. A prior art electrophoretic display device is disclosed in the article 44.3L: A Printed and Rollable Bistable Electronic Display, P. Drzaic, et al.; SID98 Digest, pages 1131-1134; 1998 (herewith incorporated by reference).

An embodiment of the system according to the invention is characterized in that the display device is a reflective display device including an interferometric modulator.

A prior art reflective display device is disclosed in the article 5.3: Digital Paper TM: Reflective Displays Using Interferometric Modulation, M.W. Miles; SID00 Digest, pages 32-35; 2000 (herewith incorporated by reference).

5 An embodiment of the system according to the invention is characterized in that the display device is a luminescent display device. A prior art luminescent display device is disclosed in US-A 6,177,767 (herewith incorporated by reference). An embodiment of the system is characterized in that the electroluminescent display device includes an organic light-emitting device.

10 An embodiment of the system according to the invention is characterized in that the display device is a field emission display device. A prior art field emission display device is disclosed in article L2.1: Late-News Paper: A.4.5-in. Fully Sealed Carbon nanotube-Based Field-Emission Flat-Panel Display, W.B. Choi et al.; SID 99 Digest, pages 1134-1137 (herewith incorporated by reference).

15 An embodiment of the system according to the invention is characterized in that the display device is a foil display device. A prior art foil display device is disclosed in the patent application WO 00/38163 (herewith incorporated by reference).

20 An embodiment of the system according to the invention is characterized in that the display device is a plasma display device. A prior art plasma display device is disclosed in the paper ISSN 1083-1312/97/1701-0281; 1997. SID; Fabrication Techniques for High-Resolution 42-Inch HDTV PDP, M. Seki et al. (herewith incorporated by reference).

25 An embodiment of the system according to the invention is characterized in that the display device is a plasma-addressed liquid crystal display device. Such a device employs with plasma display and liquid crystal display technologies, a display cell of the liquid crystal display device having with a physical electrode and a virtual electrode. The virtual electrode is formed by a charge layer produced by the plasma during operation. In this embodiment the conduction means is connected, particularly electrically connected, to the virtual electrodes via the plasma. A prior art plasma-addressed liquid crystal display device is disclosed in the article 20.4L: Late-News Paper: Development of a 42-in. High-Definition Plasma-Addressed LCD, M. Hoyashi et al.; SID 99 Digest, pages 280-283 (herewith
30 incorporated by reference).

An embodiment of the system according to the invention is characterized in that the acoustic transducer means is a loudspeaker, wherein, a vibration of a display cell is generated during use, by an electrostatic force produced by a voltage difference across the opposite electrodes of said cell. The loudspeaker includes or can be connected to an electric

driving means, particularly a voltage source. By varying the voltage across opposite electrodes a varying electrostatic force is generated for radiating sound from the display device, said force varying in a manner related to the varying voltage.

5 An embodiment of the system according to the invention, in which the acoustic transducer means is a loudspeaker, has a control means for selectively driving display cells. By selectively driving a number or all of the display cells the display device can be used as a 2D loudspeaker array, offering the possibility to direct a beam of sound generated by such an array and to control the acoustic directivity. It is possible to generate a narrow beam of sound, e.g. radiated in a main beam directly into an ear. Alternatively, it is possible to divide the array in subarrays, each producing the sound of a particular sound channel, e.g. a left and a right channel, such that stereophonic sounds be reproduced. The last-mentioned feature may be combined with technologies such as sound-base widening techniques. In other words this embodiment enables the creation of complex acoustic patterns to either focus the sound or to expand the sound image. It is to be noted that such a control means is known per se. The patent document US 4,233,472 (herewith incorporated by reference) e.g. discloses a circuit arrangement for a loudspeaker combination, the combination comprising a plurality of dynamic speakers which are arranged adjacent to each other in a continuous plane. The speakers may be arranged in line or in a two-dimensional configuration, the directivity pattern of the loudspeaker combination being determined by the circuit arrangement. Such an arrangement may be used as control means in the system according to the invention.

25 An embodiment of the system according to the invention is characterized in that the acoustic transducer means is a microphone, wherein, during use, a vibration of a display cell generates a voltage difference across the opposite electrodes of said cell. The acoustic transducer means can be a combination of a loudspeaker and a microphone.

It is to be noted further that US-A 6,137,890 discloses a portable computer piezoelectric speaker, wherein a lid of a computer device serves as a rear speaker panel and a display screen of the computer device serves as a front speaker panel and wherein a piezoelectric actuator is located at or near the middle of a speaker panel for bringing the panel into vibration in order to radiate sound.

30 The electronic apparatus according to the invention, which apparatus may be a portable small apparatus, such as a mobile telephone, or a large apparatus, such as a TV set or a monitor, includes with the sound and vision system according to the invention.

With reference to the Claims, it is to be noted that various characteristic features defined in the set of Claims may occur in combination.

The above-mentioned and other aspects of the invention are apparent from and will be elucidated, by way of non-limitative example, with reference to the embodiments described hereinafter.

In the drawings:

Figures 1 to 9 diagrammatically show several embodiments of the sound and vision system according to the invention,

Figure 10 is a block diagram relating to the sound and vision system according to the invention, and

Figure 11 diagrammatically shows an embodiment of the electronic apparatus according to the invention.

The embodiment of the sound and vision system according to the invention shown in Figure 1 comprises a liquid crystal display device 1 incorporating an acoustic transducer means, particularly a loudspeaker. The liquid crystal display device 1 comprises a pair of substrates 3, 4 of glass or the like facing each other, a layer 5 of a liquid crystal material being present between the substrates 3, 4. A plurality of electrodes 7 consisting of a transparent conductive film are formed on an inner surface of the transparent substrate 3. The other surface of the substrate 3 may form the front of the device. Electrodes 8 are present on an inner surface of the other substrate 4, such that the electrodes 8 face the electrodes 7. The electrodes 8 may form a common electrode. Two facing electrodes 7, 8 together with the liquid crystal material therebetween form a display cell 9. The display device 1 further comprises a conductive means 11 including conductive tracks and switching means, e.g. thin film transistors, for addressing the display cells 9. The loudspeaker is formed by all or a number of the display cells 9, the conductive means 11 being electrically coupled to the relevant electrodes 7, 8 to apply voltages V across said electrodes in order to cause the display cells 9 to vibrate and create an acoustic output. Such a vibration is generated by electrostatic forces working across the layer 5 of liquid crystal material. The frequency and magnitude of the acoustic output is tunable in frequency and amplitude, depending on the values of the voltages applied. It is to be noted that a number of facing electrodes may be applied to the same substrate in the so-called in-plane switching LCD.

The embodiment of the system according to the invention shown in Figure 2 comprises an electrochromic display device 101. The device 101 comprises two substrates 103 and 104, each carrying electrodes 107 and 108, respectively. An electrochromic

conducting polymer layer 112 is provided on the electrodes 108 and is in contact with an electrolyte layer 105. The layer 105 may contain a solid electrolyte or, alternatively, a liquid electrolyte. Two facing electrodes 107, 108 together with the electrolyteically conductive material of the electrolyte layer 105 and the electrochromically conducting material of the layer 112 form a display cell 109. One or several of these cells 109 form an acoustic transducer means, a conductive means 111 being electrically coupled to the acoustic transducer means for conveying signals. The transducer means may be a loudspeaker, in which case voltages are applied across one or more pairs of electrodes 107, 108 in order to generate a sound vibration of one or more display cells 109. Alternatively, the transducer means may be a microphone, in which case motions, caused by an incident sound pressure, of display cells generate changes in capacitance between facing electrodes and produce voltage differences across the relevant facing electrodes. The transducer means may even be a combination of a loudspeaker and a microphone.

The embodiment of the system in accordance with the invention shown in Figure 3 comprises an electrophoretic display device 201. The device 201 comprises two substrates 203 and 204 each carrying electrodes 207 and 208, respectively. A layer 205 including an electrophoretic display liquid 205a and particles 205b is sandwiched between the substrates 203 and 204, and is in contact with the electrodes 207 and 208. A pair of facing electrodes 207, 208 together with the material of the electrophoretic layer 205 forms a display cell 209. One or more display cells 209 constitute an acoustic transducer means, such as a loudspeaker, a conductive means 211, such as conductive tracks, being provided for electrical coupling to the acoustic transducer means, particularly the electrodes 207, 208.

The embodiment of the system in accordance with the invention shown in Figure 4 comprises a reflective display device 301. The device 301 comprises two substrates 303 and 304, each carrying electrodes 307 and 308, respectively, which electrodes are electrically connected to a conductive means 311. An interferometric modulator including a foil 305 extends in a space between the substrates 303 and 304. The foil 305 is locally fixed to spacers 313 extending between the substrates 303 in order to form foil portions 305a. Each pair of facing electrodes 307, 308 together with a sandwiched portion 305a forms a display cell 309. Such a display cell forms or is part of an acoustic transducer means.

The embodiment of the system in accordance with the invention shown in Figure 5 comprises a luminescent, particularly an organic electroluminescent, display device 401. The device 401 comprises a substrate 403 carrying electrodes 407 and a conductive means 411 electrically connected to the electrodes 407. An electroluminescent layer 405

extends between the electrodes 407 and the opposite electrodes 408. Each pair of facing electrodes 407 and 408 together with the luminescent material of the layer 405 extending between these electrodes forms a display cell 409. One or more of these display cells form an acoustic transducer means.

- 5 The embodiment of the system in accordance with the invention shown in Figure 6 comprises a foil display device 501 having two substrates 503 and 504 carrying electrodes 507 and 508, respectively, and a conductive means 511 electrically coupled to the electrodes 507 and 508. The substrate 503 is a light guide which can be illuminated by a light source 512. Spacer elements 513 are provided between the substrates 503 and 504.
- 10 Membrane or foil portions 505a of a metallic material are present in a space between the substrates 503 and 504 and extend between and are fixed to the spacer elements 513. Each pair of facing electrodes 507, 508 together with the membrane portion 505a sandwiched therebetween forms a display cell 509 of an acoustic transducer means.

- The embodiment of the system according to the invention shown in Figure 7
- 15 comprises a flat panel field-emission display 601. The device 601 includes two plate-shaped glass substrates 603 and 604, the substrates 603 and 604 carrying electrodes 607 and 608, respectively. The electrodes 607 and 608 carry a phosphor layer 612a and field emitters 612b, respectively. Spacers 613 are provided between the two substrates 603 and 604. Two facing electrodes 607 and 608 together with the phosphor layer 612a provided on the relevant
- 20 electrode 607 and the field emitters 612b provided on the relevant electrode 608 form a display cell 609. One cell or a number of these cells constitute(s) an acoustic transducer means, such as a loudspeaker. The display device 601 further includes conductive means, not shown, which are electrically connected to the electrodes 607 and 608 for, on the one hand, addressing the display cells, and on the other hand, conveying signals relating to sound.

- 25 The embodiment of the system according to the invention shown in Figure 8 comprises a plasma display device 701 including display cells 709 and conductive means electrically connected to said cells. Such a display cell 709 has a display electrode 707 and an address electrode 708 both embedded in a dielectric layer 715a and 715b, respectively, a barrier rib 713 extending between the two facing electrodes 707 and 708. A phosphor layer
- 30 712 is present in the interior of each cell 709. Each display cell 709 may form part of an acoustic transducer means.

 The embodiment of the system according to the invention shown in Figure 9 has a plasma-addressed liquid crystal display (LCD) device 801 and an acoustic transducer means, e.g. a loudspeaker, formed by display cells 809 of the device 801. A display cell 809

includes an electrode or electrode portion 807, a liquid crystal 816 and a virtual electrode 808 formed by a plasma 818 generated during operation of the device 801. Such a plasma is formed between ribs 813 by means of electrodes 819 and 820. As in the other embodiments, the device 801 is provided with a suitable conductive means for conveying signals relating to sound. In the case of a loudspeaker embodiment the conductive means is at least electrically connected to the electrodes or electrode portions 809 in order to set display cells 809 into vibration or motion to radiate sound. It is within the scope of the invention to drive each cell 809 with an individual signal, i.e. voltage, in order to control the directivity of the bundle of radiated sound. Such a measure can also be applied to the other embodiments.

10 To apply this measure, the sound and vision system, preferably its display device, is preferably provided with electronic selection or control means, including suitable circuitry for selectively driving display cells.

The block diagram shown in Figure 10 schematically shows the operation of a loudspeaker embodiment of the sound and vision system in accordance with the invention.

15 The system 1000 includes a display data driver 1002 to generate data which is transferred (arrow 1003) to appropriate sections, i.e. display cells, of a display device 1002. Switching means 1005, 1007 are included to supply the data driver 1001 with image information from an image data means 1009 and/or acoustic data from an acoustic data means 1011.

The embodiment of the electronic apparatus in accordance with the invention shown in Figure 11 is a portable telephone 1100, including an embodiment of the sound and vision system according to the invention. The telephone 1100 has a display device 1102 having a display screen 1102a and including an acoustic transducer means. The display device 1102 is a part of the embodiment of the sound and vision system according to the invention. The telephone 1100 further has a keypad 1104. The acoustic transducer means of the display device 1102 may be a loudspeaker and/or a microphone.

25 It is to be noted that the invention is not restricted to the embodiments shown. Any embodiment having a transducing means formed by a display cell, wherein the conductive means of the display device is electrically coupled to the acoustic transducer means in order to convey signals to and/or from the transducing means, is regarded as being within the scope of the invention.

30

CLAIMS:

1. A sound and vision system comprising a display device and an acoustic transducer means, which display device includes display cells having opposite electrodes and includes a conductive means connected to the electrodes in order to address said display cells, wherein the acoustic transducer means includes one or more of said display cells and
5 the conductive means is electrically coupled to the acoustic transducer means.
2. A system as claimed in Claim 1, wherein the liquid crystal layer comprises a liquid crystal material out of the group flexoelectric liquid crystals, cholestic liquid crystals and ferroelectric liquid crystals.
10
3. A system as claimed in Claim 1, wherein the display device is a liquid crystal display device including a liquid crystal layer sandwiched between substrates.
4. A system as claimed in Claim 1, wherein the display device is an
15 electrochromic display device including a material of which the color is switchable in dependence on an electric current or potential.
5. A system as claimed in Claim 1, wherein the display device is an electrophoretic display device including an electrophoretic display medium sandwiched
20 between conductors.
6. A system as claimed in Claim 1, wherein the display device is a reflective display device including an interferometric modulator.
- 25 7. A system as claimed in Claim 1, wherein the display device is a luminescent display device.
8. A system as claimed in Claim 7, wherein the luminescent display device includes an organic light-emitting device.

9. A system as claimed in Claim 1, wherein the display device is a field-emission display device.

5 10. A system as claimed in Claim 1, wherein the display device is a foil display device.

11. A system as claimed in Claim 1, wherein the display device is a plasma display device.

10

12. A system as claimed in Claim 1, wherein the display device is a plasma-addressed liquid crystal display device.

13. A system as claimed in Claim 1, wherein the acoustic transducer means is a
15 loudspeaker, a vibration of a display cell being generated during use by an electrostatic force produced by a voltage difference across the opposite electrodes of said cell.

14. A system as claimed in Claim 13, characterized by the presence of a control means for selectively driving display cells in order to control the sound directivity.

20

15. A system as claimed in Claim 1 or 13, wherein the acoustic transducer means is a microphone, a vibration of a display cell generating, during use a voltage difference across the opposite electrodes of said cell in order to control the sound directivity.

25 16. An electronic apparatus including the sound and vision system as claimed in any of the preceding Claims.

17. A mobile telephone provided with the system as claimed in any of the Claims 1 to 15.

1/4




FIG. 1




FIG. 2

2/4




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

4/4




FIG. 9




FIG. 10




FIG. 11

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 October 2002 (17.10.2002)

PCT

(10) International Publication Number
WO 02/082858 A3

(51) International Patent Classification⁷: **H04R 23/00, 7/04**

(21) International Application Number: **PCT/IB02/00973**

(22) International Filing Date: **20 March 2002 (20.03.2002)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
01201292.8 4 April 2001 (04.04.2001) EP

(71) Applicant: **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors: **AARTS, Ronaldus, M.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **JOHNSON, Mark, T.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **SCHRIJNEMAEEKERS, Hubert, J., M.**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

(88) Date of publication of the international search report:
4 December 2003

[Continued on next page]

(54) Title: **SOUND AND VISION SYSTEM**



(57) Abstract: A sound and vision system comprising a display device (1) and an acoustic transducer means, such as a loudspeaker or a microphone. The display device includes display cells (9) having opposite electrodes (7, 8) and includes a conductive means (11) connected to the electrodes in order to address said display cells. The acoustic transducer means is formed by a display cell and the conductive means is electrically coupled to the acoustic transducer means in order to convey signals, as a result of which the acoustic transducer means is an integral part of the display device.



WO 02/082858 A3



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 02/00973

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 H04R23/00 H04R7/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 H04R G02F G09G C09K H04N C07D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 00 02417 A (NEW TRANSDUCERS LTD ;AZIMA HENRY (GB); MORECROFT DENIS (GB)) 13 January 2000 (2000-01-13) page 1, line 16-28	1-7, 13, 14, 16, 17
A	page 2, line 17 -page 4, line 2 page 10, line 8 -page 12, line 24 page 14, line 25 -page 15, line 17	15
Y	EP 0 814 366 A (SEIKO INSTR INC) 29 December 1997 (1997-12-29) page 2, line 3-6 page 3, line 40 -page 5, line 6 page 6, line 49 -page 7, line 6 page 7, line 17 -page 12, line 32 page 13, line 3 -page 16, line 13 ----- -/--	1-4, 6, 7, 13, 14, 16, 17

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

23 June 2003

Date of mailing of the international search report

01/07/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Zanti, P

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/IB 02/00973

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 269 150 A (PHILIPS NV) 1 June 1988 (1988-06-01) page 2, line 1-6 page 3, line 48 -page 4, line 56 page 9, line 10-12	1,3-5, 13,14, 16,17
A	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 12, 3 January 2001 (2001-01-03) -& JP 2000 268968 A (SHARP CORP), 29 September 2000 (2000-09-29) abstract	8
A	US 6 005 342 A (MORTON DAVID C) 21 December 1999 (1999-12-21) column 3, line 23 -column 4, line 27	9
A	WO 00 31579 A (KUIJPER MAARTEN ;KONINKL PHILIPS ELECTRONICS NV (NL); PHILIPS SVEN) 2 June 2000 (2000-06-02) page 3, line 34 -page 4, line 5 page 4, line 30 -page 7, line 25	10
A	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 05, 30 May 1997 (1997-05-30) -& JP 09 009178 A (SONY CORP), 10 January 1997 (1997-01-10) abstract	11,12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 02/00973

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0002417	A	13-01-2000	AU 754818 B2	28-11-2002
			AU 4520599 A	24-01-2000
			BG 105047 A	31-12-2001
			BR 9911818 A	27-03-2001
			CA 2336271 A1	13-01-2000
			CN 1307791 T	08-08-2001
			EP 1084592 A1	21-03-2001
			WO 0002417 A1	13-01-2000
			HU 0103957 A2	28-03-2002
			JP 2002533957 T	08-10-2002
			NO 20010005 A	28-02-2001
			NZ 508511 A	28-03-2002
			PL 345317 A1	03-12-2001
			SK 20292000 A3	11-06-2001
			TR 200100136 T2	21-06-2001
			US 2001026625 A1	04-10-2001
			AU 745830 B2	11-04-2002
			AU 2926500 A	28-09-2000
			BR 0008726 A	26-12-2001
			CA 2365308 A1	14-09-2000
			CN 1342383 T	27-03-2002
			CZ 20013052 A3	16-01-2002
			EP 1159852 A2	05-12-2001
			WO 0054548 A2	14-09-2000
			HU 0200228 A2	29-05-2002
			JP 2002539698 T	19-11-2002
			NO 20014285 A	04-09-2001
			PL 350277 A1	02-12-2002
			SK 12432001 A3	03-12-2001
			TR 200102543 T2	21-03-2002
			TW 472496 B	11-01-2002
			US 6342831 B1	29-01-2002
EP 0814366	A	29-12-1997	JP 2998075 B2	11-01-2000
			JP 10239684 A	11-09-1998
			EP 0814366 A2	29-12-1997
			US 6266113 B1	24-07-2001
EP 0269150	A	01-06-1988	NL 8602698 A	16-05-1988
			AU 611647 B2	20-06-1991
			AU 8013687 A	05-05-1988
			CN 87107131 A , B	11-05-1988
			DE 3779575 D1	09-07-1992
			DE 3779575 T2	24-12-1992
			EP 0269150 A1	01-06-1988
			ES 2032815 T3	01-03-1993
			HK 142693 A	07-01-1994
			JP 2505826 B2	12-06-1996
			JP 63127291 A	31-05-1988
			KR 9609582 B1	20-07-1996
			US 4892389 A	09-01-1990
JP 2000268968	A	29-09-2000	US 6525465 B1	25-02-2003
US 6005342	A	21-12-1999	US 5866039 A	02-02-1999
WO 0031579	A	02-06-2000	WO 0031579 A1	02-06-2000
			EP 1055147 A1	29-11-2000

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 02/00973

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0031579	A	JP 2002530718 T	17-09-2002
JP 09009178 8	A	NONE	